

THINK

Scuff Tuff SG Process Series



We're Talking Tough

Beautiful color and a durable rub-resistant finish that holds out on a variety of stocks. Custom designed to perform on difficult-to-print matte, coated or uncoated stocks that tend to mark easily. It's high quality and big-time tough. You got a problem with that?

Product Overview

Scuff Tuff SG Process Series inks are formulated for printers who demand a high-quality durable finish that wears well under adverse conditions.

TOYO INK
Value You Can See

1-866-969-TOYO (8696) • www.toyoink.com





Features and Benefits

Features

- Low VOC
- Tough rub-resistant finish
- Excellent hold out on matte, coated or uncoated stock
- Fast drying

Benefits

- Easy to manage on press
- Suitable for a variety of paper finishes
- High-quality color reproduction

NOTE: Scuff Tuff is not suitable for offline applications, including foil stamping, lamination, aqueous or UV coatings. See your TOYO representative for details.

Specifications

Packaging

5 lb. can

Technical Data

	Yellow	Magenta	Cyan	Black
M Series (Medium Tack)				
Tack:	10	12	13	13
Flow:	17.5	17	16.5	17
VOC (lb/gal)				
Test Method: EPA 24	.50	.50	.50	.67
Recommended Densities for Gloss Coated Stock				
Narrow band	1.30-1.40	1.35-1.55	1.35-1.50	1.80-2.00
Wide band	0.90-1.10			

Test conditions: Tack Ink-O-Meter 800 rpm @ 90°F
Flow/Spread-O-Meter Radius (mm) / 25°C

Note: Actual tack and flow on the press vary due to ink film thickness, image area, press speed, fountain solution and also the condition of the press and pressroom. The merchandise herein contained is sold without warranties expressed or implied. These conditions shall not be waived other than by an offer of the seller in writing.



For technical assistance, call 1-866-969-8696.